



ioDIGITAL™

Technology made simple. Installation made easy.



Buy it for looks. Buy it for life.®

Introducing ioDIGITAL.™ Easy Hassle-Free Installation.

What makes ioDIGITAL so easy to install?

- Only one valve required per system.
- All ioDIGITAL valves include push-fit connectors that work easily and quickly with traditional plumbing supply tubes (PEX, CPVC and copper).
- ioDIGITAL valves fit within a traditional 2-inch by 4-inch framed wall.
- ioDIGITAL valves plug into a standard 110v power outlet than can be located in a linen closet, under the tub – up to 30 feet from the valve – for easier installation and retrofit flexibility.
- Adjusting the maximum temperature allowable is easily done on ioDIGITAL valves via a dial control. Such calibration of standard thermostatic cartridges is a more time-consuming process.
- ioDIGITAL valves do not need ventilation, but they should be mounted in an interior wall to eliminate extreme temperature conditions.
- A minimum 14-inch by 30-inch access panel is required for the spa, and a minimum 14-inch by 16-inch access panel is required for the shower and tub. ioDIGITAL valves must be installed with the front facing the access panel.



3381

ioDIGITAL shower valve

- M•PACT® common valve system
- 1/2" push-fit connectors work with CC, PEX and CPVC
- precise temperature and flow control
- fits in standard 2" x 4" wall construction
- 30' data cable connects to ioDIGITAL controller
- power cable included



3384

ioDIGITAL vertical spa valve

- requires fewer trim components (handles/knobs) to install, and only one valve
- M•PACT common valve system
- 3/4" inlet and 1/2" outlet push-fit connectors work with CC, PEX and CPVC
- 4 outlet ports
- precise temperature and flow control
- fits in standard 2" x 4" wall construction
- 30' data cable connects to ioDIGITAL controller
- power cable included



4994

ioDIGITAL roman tub valve

- M•PACT common valve system
- 1/2" push-fit connectors work with CC, PEX and CPVC
- precise temperature and flow control
- fits in standard 2" x 4" wall construction
- 30' data cable connects to ioDIGITAL controller
- power cable included



Vertical spa installation example shown

- 1 Placement flexibility**
Extremely versatile, the controller can be mounted in many different places up to 30 feet away from the valve.
- 2 Push-fit connections**
Installation is quick and easy, no soldering or threading.
- 3 Electrical box**
Compatible with standard 110v GFCI outlet.
- 4 Digital valve**
Includes power cord and 30-foot data cable for maximum flexibility.



The Moen ioDIGITAL system is certified to cUPC with applicable standards ASSE 1016 and ASME A112.18.1M/CSA B125.1 (shower valves), CSA B125.3 (Roman tub valves), ASSE1070 (Roman tub valves) and UL1951. All ioDIGITAL system components are backed by a five-year limited warranty, and the finishes and mechanical components feature a Lifetime Limited Warranty.



Buy it for looks. Buy it for life.®

Visit our web site at www.moen.com